PRODUCTINFORMATION

Made in Germany

HM MOTORENÖL 0W-40 RACE

Passenger car motor oil fully synthetic SAE 0W-40

Description

HM MOTORENÖL 0W-40 RACE is a fully synthetic high-performance engine oil of viscosity index 0W-40, offering an extremely high safety reserve for both turbocharged and non-charged four-stroke diesel and petrol engines. The high performance of **HM MOTORENÖL 0W-40 RACE** is based on the use of the latest synthetic base oil products in conjunction with a powerful additivev mixture.

Application

HM MOTORENÖL 0W-40 RACE is particularly suitable for modern petrol and diesel passenger car engines with or without turbocharging. It allows for long oil change intervals (observe manufacturer instructions!).

Properties

- low exhaust gas emissions due to the reduced fuel consumption help to protect the environment
- guarantees easy and reliable cold start even at extremely low temperatures (-30°C)
- keeps the engine clean and allows for longer oil change intervals
- ensures outstanding operational safety at both extremely low start temperature and high operating temperatures

Product data

Properties	Unit	0W-40*
Density 15 °C	kg/l	0.846
Viscosity 40 °C	mm²/s	81.2
Viscosity 100 °C	mm²/s	14.2
Viscosity index		183
COC flash point	°C	240
Pour point	°C	-48

* are average values and may vary in the framework of the standard.

Quality level

API SN/CF
ACEA A3/B4

Performance

MB 229.3
VW 502 00 / 505 00
BMW Longlife-01

Customs tariff no. 271019: Motor oils, compressor lube oils and turbine lube oils containing by weight >= 70% of petroleum oils or of oils obtained from bituminous minerals, these oils being the basic constituents of the preparations

Status September 2022