PRODUCTINFORMATION

Made in Germany

HM MOTORENÖL 10W-40 LL

Passenger car motor oil HC-synthetic based SAE 10W-40

Description

HM MOTORENÖL 10W-40 LL is a high-performance lowfriction engine oil made from synthetic hydrocracked (HC) base oils of viscosity grade 10W-40. This product is suitable for year-round use under all operating conditions. Thanks to carefully chosen, highly effective additives, this high-performance low-friction engine oil offers excellent properties.

Application

Highly recommended for modern petrol and diesel engines, including models with turbocharger in passenger cars and light commercial vehicles.

Properties

- reduced wear thanks to short engine lubrication time
- fuel savings due to low internal friction
- prevents the formation of deposits, corrosion and black sludge
- suitable for cars with prolonged oil change intervals
- observe manufacturer instructions

Product data

Properties	Unit	10W-40*
Density 15 °C	kg/l	0.867
Viscosity 100 °C	mm²/s	13.8
Viscosity index		152
COC flash point	°C	210
Pour point	°C	-39

* are average values and may vary in the framework of the standard.

Quality level

API SN/CF
ACEA A3/B4

Performance

VW 501.01/505.00
MB 229.1
RN 0700

Customs tariff no. 271019: Motor oils, compressor lube oils and turbine lube oils containing by weight >= 70% of petroleum oils or of oils obtained from bituminous minerals, these oils being the basic constituents of the preparations

Status October 2022